

MODEL	TS-25	TS-37	TS-52
Working width	600mm	900mm	1300mm
Working thickness	0.8~10mm	0.8~10mm	0.8~10mm
Minimum length of workpiece	400mm	400mm	400mm
Sanding belt specifications	25" x 75"	37" x 75"	52" x 75"
Feeding speed	3.5 ~ 9 M/min	3.5 ~ 9 M/min	3.5 ~ 9 M/min
Sanding belt Motor	20 HP x 1	25 HP x 1	30 HP x 1
Feeding motor	0.5 HP x 1	1 HP x 1	2 HP x 1
Elveation motor	0.5 HP x 1	0.5 HP x 1	0.5 HP x 1
Pump motor	0.5 HP x 1	1 HP x 1	1 HP x 1
Water tank capacity	300 L	450 L	600 L
Machine dimensions(L*W*H)	2110 x 1550 x 2500	2110 x 1850 x 2500	2110 x 2250 x 2500
Machine weight	2800 Kg	3400 Kg	4000 Kg

MODEL	TS-252	TS-372	TS-522
Working width	600mm	900mm	1300mm
Working thickness	0.8~10mm	0.8~10mm	0.8~10mm
Minimum length of workpiece	400mm	400mm	400mm
Sanding belt specifications	25" x 75"	37" x 75"	52" x 75"
Feeding speed	3.5 ~ 9 M/min	3.5 ~ 9 M/min	3.5 ~ 9 M/min
Sanding belt Motor	20 HP x 2	25 HP x 2	30 HP x 2
Feeding motor	1 HP x 1	2 HP x 1	3 HP x 1
Elveation motor	0.5 HP x 1	0.5 HP x 1	0.5 HP x 1
Pump motor	0.5 HP x 1	1 HP x 1	1 HP x 1
Water tank capacity	450 L	600 L	800 L
Machine dimensions(L*W*H)	2490 x 1550 x 2500	2490 x 1850 x 2500	2490 x 2250 x 2500
Machine weight	3400 Kgs	4200 Kgs	5200 Kgs

MODEL	TS-253	TS-373	TS-523
Working width	600mm	900mm	1300mm
Working thickness	0.8~10mm	0.8~10mm	0.8~10mm
Minimum length of workpiece	400mm	400mm	400mm
Sanding belt specifications	25" x 75"	37" x 75"	52" x 75"
Feeding speed	3.5 ~ 9 M/min	3.5 ~ 9 M/min	3.5 ~ 9 M/min
Sanding belt Motor	20 HP x 3	25 HP x 3	30 HP x 3
Feeding motor	2 HP x 1	3 HP x 1	5 HP x 1
Elveation motor	0.5 HP x 1	0.5 HP x 1	0.5 HP x 1
Pump motor	1 HP x 1	1 HP x 1	2 HP x 1
Water tank capacity	600 L	800 L	1000 L
Machine dimensions(L*W*H)	2870 x 1550 x 2500	2870 x 1850 x 2500	2870 x 2250 x 2500
Machine weight	4000 Kgs	5000 Kgs	6400 Kgs